



Ergonomic Safety Ladder System for MRO Fleet Service for the Boeing 757 Aircraft



LockNclimb ergonomic safety ladders are specifically designed for each aircraft in the fleet to provide stable working conditions for MRO technicians performing routine maintenance and repair service on the flight line, in the hanger and engine shop.



7LNCPYLON Aluminum Pylon Ladder (A)

Free-standing 7' aluminum ladder, OSHA rated 300-lb. Special Duty, 84"L X 32"W. Exceeds ANSI 14.2 specifications. Composed of aluminum construction frame 31" wide with 6061-grade aluminum base with Pylon LockNclimb frame. Commercial grade wheels mounted on sides of pylon. Folding rocker arm assembly for easier storage. Rubber padding on back rails and treads protects aircraft surfaces from damage. Rubber bumpers on side protect ladders from accidental dropping on concrete or pavement surface. LockNStands to provide durable comfortable for extended standing, and one LockNtray tool tray. Do Not Stand stickers. **Designed to service thrust reverser and fan cowl area.**



9LNCPYLON Aluminum Pylon Ladder (B)

Free-standing 9' Aluminum ladder, OSHA rated 300-lb. Special Duty, 84"L X 32"W. Exceeds ANSI 14.2 specifications. Composed of aluminum construction frame 31" wide with 6061-grade aluminum base Pylon LockNclimb frame. Commercial grade wheels mounted on sides of pylon. Folding rocker arm assembly for easier storage. Rubber padding on back rails and treads protects aircraft surfaces from damage. Rubber bumpers on side protect ladders from accidental dropping on concrete or pavement surface. Equipped with two (2) LockNStands to provide durable comfortable for extended standing, and one LockNtray tool tray. Yellow handrails provide extra safety. Do Not Stand stickers placed above safe stand area. **Designed to service upper fan cowl and thrust reverser area.**

BOEING 757: 7LNCOPYLON, 9LNCOPYLON, 11LNCOPYLON, 12WWCADET, EELITE, 14COWLPLYLON



11LNCOPYLON Aluminum Pylon Ladder (C)

11' free standing aluminum ladder, OSHA rated 300-lb. Special Duty, 132" L X 32" W. Exceeds ANSI 14.2 specifications. Composed of aluminum construction frame 31" wide with 6061-grade aluminum Pylon LockNClimb frame. Commercial grade wheels mounted on sides of pylon. Equipped with removable brass feet to allow easier sliding on concrete and/or apron surfaces. Rubber padding on back rails and treads protects aircraft surfaces from damage. Rubber bumpers on side protect ladders from accidental dropping on concrete or pavement surface. LockNStands to provide durable comfort for extended standing. LockNtray optional. Do Not Stand stickers placed above safe stand area. **Designed to service the upper engine under the fan cowl.**



12WWCADET Aluminum Gear Well Ladder (D)

12' top rested aluminum ladder, OSHA rated 300-lb. Special Duty, 132" L X 32" W. Exceeds ANSI 14.2 specifications. Composed of aluminum construction frame 31" wide with 6061-grade aluminum base wheel well frame. Commercial grade wheels mounted on sides of bottom frame. Rubber padding on back rails and treads protects aircraft surfaces from damage. Rubber bumpers on side protect ladders from accidental dropping. LockNStands to provide durable comfort for extended standing. LockNtray optional Equipped with removable brass feet to allow easier sliding on concrete and/or apron surfaces. Do Not Stand stickers placed above safe stand area. **Designed to service both sides of the wheel well and landing gear.**



EELITE Fiberglass Extension Ladder (E)

Designed to allow stable working access to the Electronic Equipment Compartment and to be an all around multi-purpose ground ladder. Lightweight Aluminum single section ladders, 60" L x 18" wide, OSHA rated 300-lb., 1-A Special Duty. Meets or exceeds ANSI 14.5 specifications. Comes complete with patented LockNClimb ladder stabilization system attached comprised of industrial quality 6061-grade aluminum. They allow close ergonomic working access to mechanical parts and fixtures within the ladder rails for easy maintenance. Padding on back top of exterior rails protect sensitive finishes. Weighs only 16 pounds. Easy to carry, set-up, fold and store. **Designed for service to fuselage belly and front access electronic equipment compartments.**



14COWLPLYLON (Optional) (F)

14' aluminum two-section ladder, OSHA rated 300-lb. Special Duty. Meets or exceeds ANSI 14.2 specifications. Composed of aluminum construction frame 31" wide with 6061-grade aluminum support base and frame. Commercial grade wheels mounted on sides of frame. Yellow safety handrails on each side of ladder rails. Rubber padding on back rails and treads protects aircraft surfaces from damage. • Rubber bumpers on side protect ladders from accidental dropping on concrete or pavement surface. Optional custom LockNStands provide durable comfortable for extended standing. Equipped with removable brass feet to allow easier sliding on concrete and/or apron surfaces. "Do Not Stand" stickers placed above safe stand area. Stickers indicate OSHA/ANSI 14.2 compliance. **Designed for service to upper pylon and thumbnail area.**



Made in the U.S.A.

Contact:
Kevin Rookes
Sales Manager Asia
LocknClimb, LLC
2500 West Laurel Street
Independence, KS 67301
kevinr@locknclimb.com
HK Mob +852 9866 1306
CN Mob +86 147 1460 5501